

SARGENT®

ASSA ABLOY

Cylinders & Components




Cylinders and Components

Table of Contents

KeyWizard™ Key Management Software.....	1
Cylinders for Bored, Auxiliary, Integra lock and Mail Box locks.....	2
Cylinder Parts: Bored, Auxiliary and Integra locks	3
40 Series Mortise Cylinders and 34 Series Rim Cylinders	4
Cylinder Parts: Mortise and Rim Cylinders	5
Cams for LFRC Mortise Cylinder and Installation Tools for 6300 & 7300 Cylinders	6
6300 Large Format Interchangeable (Removable) Core	7
7300B Small Format Interchangeable Cores	8
Old Style Removable Cores, Mortise/Rim Cylinders	9
Competitive Keyway Cylinders, Bump Resistant Cylinders, Kits and Top Loading Kits	10
124 Mortise Turn Lever Cylinders, Rosettes & Blocking Rings.....	11
Construction Master Keying Lost Ball, Split Keying Construction Keying Kit (Lost Ball)	12
Bitting Dimensions, Pins and Springs	13
Conventional, Signature and RC/UL Interchangeable Core Keying Kits and Depth Key Kits	14
Key Blanks/Key Sections, Bitting Lists	15
Visual Key Control and Tamper Proof Packaging	16
Master Keying and Cylinder Terms.....	17

Pyramid. Cylinder & Key Control Products



On The Cover

#41 Mortise Cylinder

SARGENT'S KeyWizard™ 5.5 Software Package Tracks Multiple Key Systems Including Keys, Keyholders, Locations, and Hardware Information

This comprehensive key management software package was developed for locksmiths and end-users to track detailed information. The program features easy to navigate, non-cluttered screens and uses a format similar to Microsoft® Outlook™.

Features:

- Free Technical Support at 1-800-610-1706 and system upgrades for 1 year
- Website support at www.keywizard.net
- Multi-level passwords and access levels
- Clear, easy to read screens
- Manages multiple end user key systems
- Customized query, reporting and search capability
- Global searching across multiple key systems
- Comprehensive hardware schedules
- Keyholder photos and signatures for identity verification
- Scheduled maintenance and reminders for overdue keys and back-ups
- Accurate key symbol sorting
- Multi-level key authorizations and key deposits
- Network and stand-alone versions
- Pinning calculators
- Reports options including printing in a variety of formats and e-mail
- Cylinder and key random serial ID generator
- Key authorization forms that can be printed at will
- Editable field titles
- Ability to connect to a website and search for any updates



How to Order:

Single License Version
Network Version
Demonstration Version
KeyWizard CD with new
masterkey system
(when purchased with
hardware)
KeyWizard CD with
existing key systems*

Part Number

KW-SS1
KW-SSN1
KW-DEMO1

DLKW1
DLKW2

KeyWizard replacement for KeyMinder
(Consult factory for eligibility requirements)

Single License Version **UP-KW-SS1**
Network Version **UP-KW-SSN1**

* Please consult factory for the availability of
existing systems for use with KeyWizard.

Computer System Recommendations:

REQUIRED:

- 350 MHz processor
- 60 MB hard disk space
- Windows® 7, Vista, XP, NT, ME, 2000 or 98
- 64MB Ram
- CD drive

RECOMMENDED For Better Performance:

- 500 MHz or faster
- 70 MB or more
- Windows® 7, Vista, XP, NT, ME, 2000 or 98
- 64MB Ram
- CD drive

BITTING LISTS

Paper bitting lists provided at no charge for factory corresponding keyed orders when requested at time of hardware order. An owners letter of authorization must be attached to all purchase orders. Existing key system bittings lists are also available contact key records for more information.


Cylinders for Bored, Auxiliary, Integra Lock and Mail Box Locks

Cylinders and Components

SARGENT®

ASSA ABLOY


10, 7, 6500 & 7500 (Lever) Line Standard Cylinders



Part Numbers:

C10-1 (13-3266) for all functions (except 50)
C10-2 (13-3492) for Hotel 50 function

8 and 9 Line Cylinders (Knob Locks)



Part Numbers:

C8-1 (13-2194) for all functions (except 50)
C8-2 (13-2195) for Hotel 50 function


T-Zone (11 Line) Cylinder



Part Numbers:

C11-1 (13-4145) for all functions (except 50)
C11-2 (13-4146) for Hotel 50 function

6 Line Cylinder



Part Numbers: Knob Function

C6-1 (13-3129)	S & N	All except 50
C6-1B (13-3130)	B	All except 50
C6-2 (13-3108)	S & N	50 Function
C6-2B (13-3109)	B	50 Function

4101 Mailbox Cylinder



Consult mailbox manufacturer to determine compatibility of cylinder and mailbox. 5 or 6 pin systems

- 2 cut day keys provided
- US Postal regulations prohibit master keyed cylinder

460, 470 and 480 Deadbolt & 7500 Interconnected Deadbolt Cylinders



Part Numbers: Function

C480-1 (13-3456)	454, 474, 484
C480-2 (13-3457)	7500DB, 455, 485, 487
C480-3 (13-3458)	456, 475, 486
C460-1 (13-3495)	464
C460-2 (13-3496)	465

7600 Integralock Cylinder



Part Number:

C7600-1 (13-3987)
for all functions
(except 26, 27, 50)

5 and 5500 Line Cylinders



Part Numbers:

C5500-1 (13-3526)
for all functions
(except 5 line 50)
C5500-2 (13-3708) 5 line
50 function hotel

758/858 Padlock Cylinder



Part Numbers:

C750-1 for
758/858 Padlocks
04 Finish only

1655 Locker Lock Cylinder



Part Numbers:

C1655-1
13-1813 (tail piece)

All cylinders are 6 pin and are supplied with 2 nickel silver keys unless noted.
When cylinders are ordered keyed to 5 pin systems, the (6th) last chamber will be empty.
Cylinder finishes: 4 and 15.

For cylinders in competitive keyways, see Page 10.

Cylinders are supplied random keyed unless specified 1 bitted or master keyed. For master keyed orders provide keying details as requested on SARGENT Keyed Order Lead Sheets, located in the price book or contact customer service.


Cylinders ordered from SARGENT Turbo program are supplied as 1 bitted as standard unless otherwise specified.

Cylinder Parts: Bored, Auxiliary and Integra Locks

Cylinders and Components

SARGENT®
ASSA ABLOY

Hotel Function Not Shown



Item	Description	Lock Line	Part Number	Comment
1	6 Pin Key Blank		See Table Page 16	
2	Plug Plug Plug Plug Plug & Pin Assembly Plug & Ring Assembly	7600 470, 480, 1655, 7500 460 5500 7, 8, 9 Knobs 6, 7 Lever, 8L, 10, 11, 6500, 7500, 758, 858	13-0090 13-0874 13-0904 13-0920 13-3425 13-3142	New 7600 Only
3	Shell Only Cylinder Shell & Slide Assembly Without Pins & Springs	7600 7, 8L, 10, 11 Levers, 758, 858 7, 8, 9 Knobs 6, 6500 460, 470, 480, 1655 5500	13-1139 13-3257 13-2048 13-3257 – Effective 9/03 13-3493 13-3514	7600 (No Slide) Illustration Shows Slide Disassembled
4	Bottom Pin	All Cylinders	See Table Page 14	
5	Top Pin	All Cylinders	13-0059	Pin No. 10 (Length .200)
6	Master Pin	All Cylinders	See Table Page 14	
7	Compression Spring	All Cylinders	13-0265	
8	Plug Retainer Plug Retainer Ring	5 7, 8, 9 Knob Plug manufactured prior to March 2005	01-0870 06-0166	
	Plug Retainer Ring	6, 7 Lever, 8L, 10, 11, 6500 and 8 line knob manufactured after April 2005	13-0205	
	Plug Retainer Ring	5500	01-0870	
9	60-70 Tail Piece 70 Tail Piece 60 Tail Piece 70 Tail Piece 70 Tail Piece 70 Tail Piece 70 Tail Piece 60 Tail Piece Tail Piece Tail Piece Tail Piece Tail Piece Tail Piece Tail Piece Tail Piece	60-70 6500 70-6500 60-7, 10 70-7, 10 70-7, 10 70-7, 10 70-7, 10 60-11 11 7, 8L, 10, 6500 6 (S & N Knobs) 6 (B Knob) 5500 758, 858	05-0033 05-0034 10-0239 10-0239 10-0240 10-0286 10-0287 11-0170 13-1385 13-0895 13-0907 13-0908 13-0919 13-1230	6 Pin Only 7 Pin Only Except 54 Function 6 Pin Except 54 Function 7 Pin Except 54 Function 6 Pin 54 Function 7 Pin 54 Function All Functions Except 50 Function 05, 24, 37, 38-2, 44
10	Cylinder Cap Spring	460, 470, 480, 1655	13-1555 – Effective 6/03 13-0693 – Prior to 6/03	
11	Cylinder Cap Pin	460, 470, 480, 1655	13-1554 – Effective 6/03 13-0691 – Prior to 6/03	
12	Cylinder Tail Washer	484 464, 465, 485, 486, 487, 1655	13-0882 13-0883	
13	Cylinder Endcap	480, 1655 460	13-0875 13-0903	
14	Tail Piece	464, 474, 484 465, 485, 487 475, 486	13-0878 13-0880 13-0881	1-3/4" to 2" (44mm to 51mm) Door Thickness
15	Blocking Piece	460, 470, 480, 1655	13-0884	
16	Slide (Mfg prior to 06-2008)	7 Old, 7, 8, 8L, 9, 10, 11, 6500 7600	13-0779 13-0816	
16	Slide (Mfg after 06-2008)	7, 8, 9, 10, 11, 1655, 6500	13-1341*	
17	Tail Piece Retainer	6, 7, 10, 11, 6500	13-0680	
18	Cam Connector	1655	13-1813	

* See page 10 for Details

40 Series Mortise Cylinders & 34 Series Rim Cylinders


Cylinders and Components

SARGENT®
ASSA ABLOY

40 Series Mortise Cylinder

- Cylinder: Solid brass, 1-5/32" (29mm) diameter
- Cap: Brass, bronze or stainless steel
- Furnished standard with No. 97 rosette and compression spring
- Optional Collars/Spacers available and ordered separately, refer to product catalogs for additional information
- See Cam Chart on Page 6 for cam required
- 6 pin standard; for 7 pin specify "7 pin", size 42 minimum
- No. 41 cylinder not available in 7 pin
- Mortise cylinder assemblies that are ordered without hardware are supplied with standard SARGENT offset cam 13-0664
- Cylinder finishes: 3, 4, 9, 10, 10B, 10BL, 15, 20D, 26, 26D, 32, 32D
- Plug finishes: 4, 15

Length under cylinder head										
Cylinder No.	41	42	43	44	46	48	50	52	54	56
Dim. X	1-1/8" (29mm)	1-1/4" (32mm)	1-3/8" (35mm)	1-1/2" (38mm)	1-3/4" (44mm)	2" (51mm)	2-1/4" (57mm)	2-1/2" (64mm)	2-3/4" (70mm)	3" (76mm)



50-40 Series Hotel Type Cylinder

Features same as standard 40 Series cylinders except:

- For use with 7850 or 8250 lock only
- 6 pin only
- Contact factory for compatibility requirements for existing 6 pin systems
- Uses only cam #115 (13-2045)
- Guest and Master keys will only retract the latch bolt but not project or retract the dead bolt
- Emergency keys (catalog # 7268 EMK) retract the latchbolt and deadbolt and can also project the deadbolt
- C Series keyways supplied standard, specify if different keyway is required. On 1 bitted or KD, CA key way will be supplied if not otherwise specified
- Consult Sargent Key records dept. when adding Hotel cylinders to existing key systems for compatibility
- Length under cylinder head (Dim. X)
- 50-43 1-3/8" (35mm); 50-44 1-1/2" (38mm)


78-40 Series Exposed Shell Only Cylinders

- Cylinder: Solid brass, 1-5/32" (29mm) diameter
- 6 pin standard, for 7 pin specify "7 pin"
- For use with SARGENT mortise locks with Escutcheon Trim (KE 3/4, LE 3/4) only
- See Function Table on Page 6 for cam required
- 78-41 6 pin; single cylinder function only except 50
- 78-42 6 or 7 pin; single cylinder functions only
- 78-43 6 or 7 pin; all functions except 50
- Plug finishes: 4, 15

34 Series Rim Type Cylinder

- 27/32" (21mm) screw pattern for through-bolted SARGENT exit devices
- Cylinder: Solid brass
- Cap: Brass, bronze or stainless steel
- Furnished standard with No. 97 rosette and compression spring, "break-off" screws and back plate
- 6 pin standard, for 7 pin specify "7 pin"
- Horizontal tail piece only
- Cylinder finishes: 3, 4, 9, 10, 10B, 10BL, 15, 20D, 26, 26D, 32, 32D
- Plug finishes: 4, 15

No. of Pins	Door Thickness when used with outside trim	Dim. A (Min.)	Dim. B (Min.)
6	2-3/8" to 3-1/4" (60mm to 82mm)	1-1/16" (27mm)	2-3/8" (60mm)
7	2-1/2" to 3-1/2" (64mm to 89mm)	1-7/32" (31mm)	2-3/8" (60mm)



All cylinders are standard 6 pin and are supplied with 2 nickel silver keys unless noted. In cylinders ordered for 5 pin systems, the (6th) last chamber will be empty.

For cylinders in competitive keyways, see Page 10.

Cylinders are supplied random keyed unless specified 1 bitted or master keyed. For master keyed orders provide keying details as requested on SARGENT Keyed Order Lead Sheets, located in the price book or contact customer service.

Cylinder Parts: Mortise and Rim Cylinders


Cylinders and Components

34 Rim/40 Series Mortise Cylinder Parts

Item	Description	Part Number	Where Used	Comment
1	Plug	See Table Below	40 Mortise & 34 Rim	
2	Cylinder Shell, Cap & Slide Assy.	See Table Below	40 Mortise & 34 Rim	Illustration Shows Slide Disassembled
3	Bottom Pin	See Table Page 13	40 Mortise & 34 Rim	
4	Master Pin	13-0062	40 Mortise & 34 Rim	Pin No. 10 (Length .260)
5	Top Pin	See Table Page 13	40 Mortise & 34 Rim	
6	Compression Spring	13-0265	40 Mortise & 34 Rim	
7	Cam	See Table Page 6	40 Mortise	
8	Screw	01-1121	40 Mortise	#3-48 x 5/16" (8mm) PH. FL.
9	Plug Retainer	13-0080	34 Rim	
10	Tail Piece	13-0085	34 Rim	
11	Cylinder Back Plate	13-0086	34 Rim	
12	Connecting Screws Standard Connecting Screws	13-0075 13-0074	34 Rim 34 Rim	#12-24 x 2-5/8" (67mm) #12-24 x 2-1/8" (54mm)
13	6 Pin Slide 7 Pin Slide	13-0779 13-0780	40 Mortise & 34 Rim 40 Mortise & 34 Rim	Mfg prior to 06-2008* Mfg prior to 06-2008*
13	6 Pin Slide 7 Pin Slide	13-1341 13-1797 v	40 Mortise & 34 Rim 40 Mortise & 34 Rim	Mfg after 06-2008* Mfg after 06-2008*

* See page 10 for Details

Standard Cylinders (Hotel Function Not Shown)








No.	Cylinder Length	6 Pin Plug Part Number	7 Pin Plug Part Number	6 Pin Shell & Slide Assy. Part Number	7 Pin Shell & Slide Assy. Part Number
34	—	13-0090	13-0587	13-2005	13-2712
41	1-1/8" (29mm)	13-0401	N/A	13-2005	N/A
42	1-1/4" (32mm)	13-0402	13-0631	13-2006	13-2765
43	1-3/8" (35mm)	13-0632	13-0632	13-2766	13-2766
44	1-1/2" (38mm)	13-0633	13-0633	13-2767	13-2767
46	1-3/4" (44mm)	13-0634	13-0634	13-2768	13-2768
48	2" (51mm)	13-0635	13-0635	13-2769	13-2769
50	2-1/4" (57mm)	13-0636	13-0636	13-2770	13-2770
52	2-1/2" (64mm)	13-0637	13-0637	13-2771	13-2771
54	2-3/4" (70mm)	13-0638	13-0638	13-2772	13-2772
56	3" (76mm)	13-0639	13-0639	13-2773	13-2773

Cams for Mortise Cylinder and Installation Tools for 6300 & 7300 Cylinders






Cylinders and Components

SARGENT®
ASSA ABLOY

Cams For Conventional Mortise Cylinders* in SARGENT Keyways

				
Standard Cam (13-0664)	#105 (13-0665)	22-Standard (13-0662)	22-105 (13-0663)	#115 (13-2045)
Standard open slotted cam provided on all 40 Series - standard. Except: 16, 50 & 92 function Mortise Locks	Short cam used for 16 & 92 function locks (Inside Cylinder) (Was -3 & -8)	Cam used for Construction Key Systems (22-), except for 16 & 92 function inside cylinder & 50 function mortise locks	Cam used for Construction Key Systems (22-), 16 & 92 function mortise locks (Inside Cylinders)	Cam used for Hotel (7850/8250) function cylinders (was -2)

Miscellaneous Cams*

				
#101 (13-0512)	#104 (13-0513)	#113 (13-0921)	#106 (13-0938)	#112 (13-0097)
Adams Rite 1850, 4700	Adams Rite 4070, 4350, 4250, 4516, 4150	SARGENT 4370 Series key switches	"Open" Schlage "L"	"Open" Misc.

* Two screws attach cam to cylinder, order as an 01-1121, when needed

432 RC 6300 Large Format Interchangeable (Removable) Core Installation Tool











432 IC 7300 Small Format Interchangeable Core Installation Tool



- The 432 RC and 432 IC are tools to assist in installing SARGENT Large Format Interchangeable (Removable) Core and Small Format Interchangeable Core Mortise Housings. These tools make it easy to thread a cylinder body into a Mortise lock and can also help check the cylinder function in a lock before installing the cylinder core.
- Order: 432 RC for the SARGENT Large Format Interchangeable (Removable) Core Installation Tool
- Order: 432 IC for the Small Format Interchangeable Core Install Tool

Cams for 6300 Large Format Interchangeable (Removable) Core Mortise Cylinders (Factory assembled to housing)

- 6300 Cams are factory installed and are not removable
- 6300 Cams are not sold separately
- Specify required Cam as a suffix: 63-44-105 cam
- For Standard Cam: No Suffix is required

	Standard 6300 Series Cam		-105 Cam for 6300 Series 16 & 92 function locks
	-115 Cam for 6300 Series 50 function locks		-101 ADAMS RITE 1850 4710
	-104 ADAMS RITE 4050, 4150, 4250, 4350, 4070, 4516		-113 4370 Series key switch
	-106 Schlage "L"		-112 Wide Straight

6300 Series Large Format Interchangeable (Removable) Cores Cylinders and Components

SARGENT®
ASSA ABLOY


60- Prefix Disposable Plastic Core



- During the construction phase in non restricted areas, disposable plastic cores can be used, eliminating use and distribution of the actual keys
- Once construction is near completion, the permanent keyed cores will be installed and the building secured; permanent keyed cores are ordered separately as 6300 Cores
- Disposable cores are available for Mortise, Exits and most cylindrical lock sets
- Operate with coin or flat screw driver
- One piece design allows for easy installation
- To order separately: Use p/n 13-5177
- Mortise Sizes available: 60-42, 60-43, 60-44 & 60-46
- Available 6300 Mortise Cams on Pg 6
- Specify required Cam as a suffix: 60-44-105 cam
- For Standard Cam: No Suffix is required
- Plastic Cores p/n is 13-5177


64- Prefix Construction Keyed Large Format Interchangeable (Removable) Core Keyed Cylinders

- The SARGENT 6400 interchangeable brass construction core enables doors to be locked during project construction period
- Using 6400 cores prevents keys for the permanent key system from becoming available during the construction process
- After construction is completed, the 6400 brass cores are removed and replaced with 6300 keyed-permanent interchangeable Cores
- A special control key releases the locking sleeve of the cylinder core allowing immediate removal of the core
- Construction cores are all keyed alike in one KA keyset
- Furnished with 6 keys and 1 control as standard
- Plug face dimpled for easy identification
- Order as a 64- prefix with products
- Mortise Sizes available: 64-42, 64-43, 64-44 and 64-46
- Available 6300 Mortise Cams on Page 6
- Specify required Cam as a suffix: 64-44-105 cam
- For Standard Cam: No Suffix is required



6300 Permanent Large Format Interchangeable (Removable) Cores Cylinders

- SARGENT LFIC (Removable) Core Cylinders and Master Key Systems are available for a quick change of cylinders for increased security. It is not necessary to remove the lock from a door to rekey the opening
- Special "control" key is used to release a locking cam allowing immediate removal of the core
- Available for use in many SARGENT products (Exit Devices, Mortise locks, Bored locks and padlocks)
- LFIC Key Systems can also include conventional cylinders operated by the same Master/change keys when the 6300 quick change feature is not needed.
- Can be master or grand-master keyed
- 2 Change keys provided
- 6 pin standard
- 1 bitted available for field keying
- 1 bitted cylinders supplied with 2 key blanks, pins and springs in chambers in 3 and 4 only.
- HA keyway will be supplied unless otherwise specified.
- Wide variety of master key systems available
- Permanent (keyed Large Format Interchangeable) cores supplied with hardware unless specified otherwise
- Available in the following SARGENT keyway families: A, B, C, G, H, K, L, N, R, and V
- Also available in the following single key sections: CR and S
- Control key is 6272 CTL, ordered separately
- Finishes: 4, 15
- Ordering as a: 6300 LFIC Core x finish and give all keying information



65-6300 Unassembled Core Only

- Unassembled core for field rekeying. Includes Control Sleeve and two key blanks
- Springs and pins to be ordered separately (see Pages 14 & 15)
- 65- Prefix - Uncombine Cores
- Finishes: 4, 15
- HA key way will be supplied standard, unless otherwise specified
- Order as: 65-6300 x finish x keyway (6 pin only)

6300 Series Parts Only

- 13-0795 Plug, Finishes: 4, 15
 - 13-3424 Inner Shell & Slide Assy, Finishes: 4, 15
 - 13-0796 Control Sleeve
 - 01-0660 Plug retaining ring
 - 13-0797 Slide for Cylinders with a box around the word SARGENT (Mfg prior to 4/06)
 - 13-1341 Slide for Cylinders WITHOUT a box around the word SARGENT (Mfg after 3/06)
- For pins, springs & keying kits see Pages 14 & 15.

63-34 Rim Cylinder

- Housing: Solid brass
- Cap: Brass, bronze or stainless steel
- Furnished standard with No. 97 rosette and compression ring
- Includes the same tailpiece and screw hole pattern as the #34 cylinder
- Finishes: 3, 4, 10, 10BL, 20D, 26, 26D, 32, 32D
- Order as: 63-34 x Finish
- Also available: 60-34 & 64-34 Rim Cylinders

63-40 Series Mortise Cylinders Standard & Hotel Function Cylinders



- Cylinder: Solid brass 1-5/32" diameter
- Cap: Brass, bronze and stainless steel
- Furnished standard with No. 97 rosette and compression ring
- Optional Collars/Spacers available and ordered separately, refer to product catalogs for additional information
- HA Standard Keyway (Except Hotel)
- For use in Sargent 78/8250s hotel function only, "C" series keyway supplied standard, unless otherwise specified. Offered in 50-63-43 size only (1-3/8") with 115 cam only.
- Hotel emergency key is 7269 EMK, ordered separately
- Order hotel cylinders as 50-63-43 or 50-60-43 which will include the 115 cam as standard
- Other SARGENT keyways available
- Mortise Sizes available: 63-42, 63-43, 63-44 & 63-46
- Available 6300 Mortise Cams on Pg 6
- Specify required Cam as a suffix: 63-44-105 cam
- For Standard Cam: No Suffix is required
- Finishes: 3, 4, 9, 10, 10B, 10BL, 15, 20D, 26, 26D, 32, 32D
- Order as: 63-42 x Finish
- 60-42 same as above, but supplied with plastic disposable plastic core

63-40 Series Mortise Cylinder Sizes


Cylinder #	63-42	63-43	63-44	63-46
Length	1-1/4" (32mm)	1-3/8" (35mm)	1-1/2" (38mm)	1-3/4" (44mm)

436-1 Slide Block Kit

- Includes fixture and staking tool for use only with the (10)- 6300 Series Cylinders manufactured after March 2006 for the ease of top loading in the field
- The kit includes 100 each slides p/n 13-1341, Staking Block and staking tool
- Cylinders manufactured after March 2006 will not include the box around the SARGENT logo and can be used with this kit



Cores without a box around the word "SARGENT"



7300B Small Format Interchangeable Cores

Cylinders and Components

SARGENT®
ASSA ABLOY

73- & 73-7P Series Small Format Interchangeable Core Cylinders 6 & 7 Pin

- SARGENT Interchangeable Core Cylinders and Master Key Systems are available for a quick change of cylinders for increased security. It is not necessary to remove the lock from the door to rekey the opening
- SARGENT 7300B Interchangeable Cores are available in SARGENT 4A and 4B keyways as well as the following standard competitor keyways: A, B, C, D, E, F, G, H, J, K, L, M. SARGENT will extend any key system after receipt of an existing bitting list from the end user
- New key systems are available in either 4A or 4B keyways. 4A in a 2 step system will be supplied standard on new systems
- A2 or A4 systems available

For hardware to be supplied with keyed cores use 73- prefix for 6 pin cores and 73-7P for 7 pin permanent cores provided

7300B Keyed Interchangeable Core

- Supplied keyed with two nickel silver change keys as standard
- Face includes SARGENT logo
- If Control keys are required order as 6282BCTL for 6 pin systems or 7282BCTL for 7 pin systems
 - 6 pin system master keys are ordered as 6282BMK
 - 7 pin system master keys are ordered as 7282BMK
- Finishes: 4, 15
- Order separately as:
7300B x Finish (for 6 pin)
7P-7300B x Finish (for 7 pin)

65-7300B Uncombined Interchangeable Cores

- Cores for field keying
- No pins, springs or key blanks provided
- No logo on face
- 65- Prefix - Uncombine Cores
- Finishes: 4, 15
- Order as:
65-7300B x Finish (for 6 pin)
65-7P-7300B x Finish (for 7 pin)



65-7300B Shown

70- Prefix Disposable Plastic Construction Core For SFIC

- Used for doors that do not require key locking during the construction period
- Operate with coin or flat screw driver
- Mortise and rim cylinders accepts either 6 or 7 pin permanent cores. Cylindrical lock sets ships with plastic core and 6 pin tail piece installed while the 7 pin tail piece is packed loose with the lock set.
- One piece design allows for easy installation
- To order separately use p/n 13-5176



72- Prefix Brass Interchangeable Construction Core

- SARGENT 7200 Interchangeable brass construction core (order 72-prefix with your SARGENT products) enables doors to be locked during the project construction period
- Using 7200 cores prevents keys for the permanent key system from becoming available during the construction process
- After construction is completed, the 7200 brass cores are removed and replaced with 7300 keyed-permanent interchangeable cores
- Plug face is blue for easy identification
- A special Construction Control key 6254 B CTL releases the locking sleeve of the construction core and allows for immediate removal of the core
- Construction cores are 6 pin and keyed alike construction master 6282 B CMK
- Six (6) change keys and one (1) Control key is included
- Cores shipped with hardware

Key Blanks/Cut Master Type Keys (Nickel Silver)

- 6 pin key blank - order as 6285B x keyway
- 7 pin key blank - order as 7285 B x keyway
- Packed 50 per box
- SARGENT Keyways: 4A, Restricted 4B Competitors: A, B, C, D, E, F, G, H, J, K, L, M
- Cut 6 pin master key, order as cat #6282BMK
- Cut 7 pin master key, order as cat #7282BMK
Cut 6 pin control key order as cat. #6282BCTL
Cut 7 pin control key order as cat. #7282BCTL

73-34 Rim Cylinder

- Brass cylinder and housing
- Furnished with No. 97 rosette, break off screws and back plate
- Optional Collars/Spacers available and ordered separately, refer to product catalogs for additional information
- Housing accepts 6 or 7 pin core
- Mounting holes located to match SARGENT hardware
- Finishes: 3, 4, 26, 26D



73-43 or 73-46 Series Mortise Cylinders

- Two cylinder sizes
- #43, 1-3/8" (35mm) length under cylinder head including cam
73-43 (6 pin)
73-7P-43 (7 pin),
70-43 housing less core
- #46, 1-3/4" (44mm) length under cylinder head including cam
73-46 (6 pin), 73-7P-46 (7 pin)
70-46 housing less core
- 1-5/32" (29mm) diameter housing
- Furnished with No. 97 cylinder rosette as standard
- Optional Collars/Spacers available and ordered separately, refer to product catalogs for additional information
- Cam is permanently staked to housing
- Housing accepts 6 or 7 pin cores
- Mortise cylinder cams operate current SARGENT hardware
- Hotel Function not available
- Finishes: 3, 4, 9, 10, 10BL, 20D, 26, 26D



Old Style Removable Cores

Mortise/Rim Cylinders

Cylinders and Components

SARGENT®
ASSA ABLOY

51- Prefix Old Style Removable Core Cylinder

- SARGENT Removable Core Cylinders and Master Key Systems are available for a quick change of cylinders for increased security. It is not necessary to remove the lock from the door to rekey the opening
 - Special "control" key is used to release a locking cam to allow immediate removal of the core
 - Available for use only in SARGENT products, such as exit devices or mortise locks, which use rim or mortise cylinders
 - SARGENT Offset Cams only
 - Available for existing systems only
 - Can be master or grandmaster keyed
- Note:** If ordering for existing construction key system, provide all keying information.
- Consult factory for existing system compatibility
 - Plug finishes: 4, 15
 - Finishes: 3, 4, 9, 10, 10B, 20D, 26, 26D, 32, 32D



Removable Core Cylinders

Mortise Type

Series	No. Pins	Length under cylinder head including cam				
		1-1/8" (29mm)	1-1/4" (32mm)	1-3/8" (35mm)	1-1/2" (38mm)	1-3/4" (44mm)
040 Cylinder	6	N/A	042	043	044	046
140 Cylinder	7	N/A	142	143	144	146
040 Core Only	6	N/A	5042	5043	5044	5046
Core Only	7	N/A	5142	5143	5144	5146

Rim Type

Series	No. Pins	Maximum overall length
134-6 pin Cylinder	6	3-3/4" (95mm)
134-7 pin Cylinder	7	3-3/4" (95mm)

Furnished standard with No. 97 rosette, "break off" screws and back plate.

Rim Type "Core Only"

	No. Pins
5134-6 pin	6
5134-7 pin	7

Note: These cylinders use the last chamber for the control sleeve. Standard keys contain a cut in this position to engage the control function.

52- Prefix Old Core Style Construction Removable

- A separate order for permanent cores, with keysets keying information, door and item numbers, should accompany the lockset order. The permanent cores will be shipped directly to the distributor and not to the job site.
- All locks ordered with removable construction core cylinders will be invoiced at the regular price established for 51- prefix
- A separate invoice will be issued to cover the permanent cores at prices listed for removable cores
- Plastic disposable cores not available

How to Order

Mortise Add 52- prefix to removable core cylinder number (Example: 52-142)
Not available for functions 50 and 52

Rim Type Add 52- prefix to removable core cylinder number (Example: 52-134)

To order removable cores only for mortise and rim type cylinders, add 52- prefix to core designation (Example: 52-5142 or 52-5134)

Competitive Keyway Cylinders, Bump Resistant Cylinders, Kits and Top Loading Kits

Cylinders and Components

SARGENT®
ASSA ABLOY

Conventional Mortise and Rim Cylinders

SARGENT offers cylinders in other manufacturers' keyways. They can be ordered as a prefix for hardware or ordered separately by part numbers. The following product lines are available with SC- and SE- prefixes:

- #41 Mortise Cylinder applications only
 - 7800/8200 Mortise Locks
 - KP8200 Keypad Operated Product
 - 4870 Deadlock
 - 20, 30, 80 and 90 Series Exit Devices
- #34 Rim Cylinder applications
 - KP8877 Keypad Operated Products
 - 8877 Profile Series Access Control Products
 - 20, 30, 80 and 90 Series Exit Devices
- All cylinders 0 bitted and supplied with two brass key blanks as standard. Hotel function not available.
- Mortise and rim cylinders supplied without SARGENT logo on face of cylinder and with No. 97 rosette when ordered without hardware
- Optional Collars/Spacers available and ordered separately, refer to product catalogs for additional information
- Mortise cylinders only supplied with SARGENT offset cam similar to 13-0664. Rim cylinders only with SARGENT mounting screw locations. Separate parts not available for these cylinders.
- Master keyed cylinders not available
- All mortise cylinders 1-1/8" (29mm) long with standard 1-5/32" shell diameter
- Finishes: 3, 4, 10, 10B, 26, 26D

Cylinder Type	Keyway	
	Schlage "C"	Schlage "E"
Mortise #41	13-3635	13-3636
Rim #34	13-3624	13-3625

How to Order

Part number x SC or SE #34 or 41 x Schlage keyway type
Example: 13-3635 x SC #41 x Schlage C keyway

Conventional Bored/Cylindrical Lock Cylinders

The following cylinders can be ordered in competitor's keyways.

- All cylinders 0 bitted and supplied with two brass key blanks as standard. Hotel function not available.
- Cylinders include tail pieces
- Finishes: 4, 15

Lock Line	Keyway	
	Schlage "C"	Schlage "E"
7, 10, T-Zone (11) & 6500	13-3613	13-3614
470/480 Deadlock	13-3651	13-3652
5	13-4116	13-4117
5500 in 04, 05 & 37 Functions	13-3662	13-3663

How to Order

Part number x SC or SE x finish Schlage keyway type
Example: 13-3614 x SE x 26 Schlage E keyway

SARGENT Bump Resistant Cylinders

These cylinders employ specially engineered patent pending components designed to resist bumping while maintaining the cylinder's strength.

Bump resistant cylinders offer these features:

- Added line of defense against intruders
- Prevents unauthorized entry

The bump resistant feature is available for the following cylinders (6 and 7 pin only):

- Mortise Cylinders:
Conventional and XC (11-)
- Rim Cylinders:
Conventional and XC (11-)
- Bored Cylinders:
Conventional and XC (11-)



BR is marked on the cylinder slide to identify Bump Resistant Cylinders

Specify bump resistance by adding BR Prefix.

How to order example: BR-10G04 LL 26D

437BR Bump Resistant Re-Pinning Kit

The 437BR Kit is used to convert existing cylinders into bump resistant cylinders. Simply replace the drivers and springs in all chambers. Each kit includes 300 pins for use in mortise/rim cylinders, 300 pins for use in KIK/KIL cylinders and 600 springs.



436-1 Top Loading Tool Kit

Top loading feature for conventional cylinders simplifies the repinning process. The dovetail cut at the top of the cylinder body allows the slide to be "peeled" off easily, without removing the barrel from the cylinder. These conventional cylinders can be easily identified with the "figure eight" marking on the back of the cylinder body (Shown).


436-1 Kit is used for top loading of Large Format Interchangeable (Removable) Cores or Conventional Cylinders

This Kit includes the following components:

- Staking Block
- Staking Tool
- 100 Slides (6 Pin)

Addition Slides Available:
7 Pin slides (Part#13-1797)
6 Pin slides (Part#13-1341)
ordered separately

Top Loading cylinders also offer additional stamping providing cylinder identification concealed for security purposes



124 Turn Lever Cylinders Rosettes & Blocking Rings

Cylinders and Components

SARGENT®
ASSA ABLOY

124 Series Turn Lever

- Used in mortise locks in lieu of cylinders when keyed cylinders are not required
- Furnished standard with No. 97 cylinder rosette when ordered separately
- Optional Collars/Spacers available and ordered separately, refer to product catalogs for additional information
- Cylinder: Brass
- Turn lever: Brass or bronze
Cap: Brass, bronze, stainless steel
- Finishes:
4, 10B, 26D



No.	124-41	124-42	124-43	124-44	124-46
Length Including Cam (Dim. x)	1-1/8" (29mm)	1-1/4" (32mm)	1-3/8" (35mm)	1-1/2" (38mm)	1-3/4" (44mm)

Cam No. Suffix Description

None	Sizes 41, 42, 43, 44 & 46 for standard offset SARGENT cam
-101	Sizes 41, 42, 43, 44 & 46 x cam for Adams Rite 1850 lock
-104	Sizes 41, 42, 43, 44 & 46 x cam for Adams Rite 4050, 4150, 4070, 4250 and 4350 locks
-105	Sizes 41, 42, 43, 44 & 46 x cam for inside of 16 and 92 mortise lock
-106	Sizes 41, 42, 43, 44 & 46 x cam for Open Schlage L
-112	Sizes 41, 42, 43, 44 & 46 x cam for Open Misc.
-113	Sizes 41, 42, 43, 44 & 46 x cam for 4370 Series Keyswitches

No. 1KB Rosette



- Used with 8200 Series mortise locks and No. 90 blocking rings when cylinders project from door
- Free spinning to protect cylinder from vandalism
- Consult 8200 series catalog for Rosette application details
- Furnished standard with 8200 LN and L rose design mortise trim
- Cast brass, bronze or stainless steel
- 1-1/2" (38mm) diameter, includes compression spring
- Projection from door:

1KB-1	5/16" (8mm)
1KB-2	7/16" (11mm)
1KB-3	9/16" (14mm)
1KB-4	11/16" (16mm)
- Finishes: 3, 4, 10, 10B, 10BL, 20D, 26, 26D, 32, 32D

No. 97 Rosette



- Standard for cylinders ordered separately from hardware
- Standard for 4800 dead bolts and 7900 and 7800 series mortise locks
- Brass, bronze or stainless steel
- 1-11/16" diameter (43mm), 9/32" (7mm) projection, includes compression spring
- Finishes: 3, 4, 10, 10B, 10BL, 20D, 26, 26D, 32, 32D

No. 90 Blocking Ring



- Used with 1KB-2 and 1KB-3 rosettes as spacer when mortise cylinder projects from face of door as shown above
- Consult 8200 series catalog for Blocking ring application details
- Brass, bronze or stainless steel
- 1-3/8" (35mm) diameter; available in thickness of 1/16", 1/8", 3/16", 1/4" and 3/8"
- Specify thickness when ordering: Order as a #90 x 3/16" for the thickness needed
- Finishes: 3, 4, 10, 10B, 10BL, 20D, 26, 26D, 32, 32D

Cylinder Nut Wrench




This wrench simplifies the installation and removal of mortise cylinders nuts used on 700 Series Auxiliary Control (80 Series ET Trim).

- Part number 97-0568

Note: Hardware ordered less cylinder will be provided with the standard collar and/or blocking rings for the standard 1-1/8" mortise cylinders.

When using cylinders that are longer consult individual catalogs to order proper size collars and/or spacers.



Construction Master Keying Lost Ball, Split Key Construction Keying Kit (Lost Ball)

Cylinders and Components

SARGENT®
ASSA ABLOY

21- Prefix Lost Ball Construction Keying

Cylinders ordered in SARGENT keyways with construction keying will include the 21- prefix Lost Ball feature as standard. This replaces the 22- split key, only available as additions to existing 22- mastered keyed systems. The 21- is not available with old or new style removable/interchangeable core (5100 & 6300s). If construction keying is required for removable/interchangeable cores, use 52- or 64- construction keyed cores.

With the lost ball option, construction keying is obtained easily without going back to each cylinder and removing the construction split key when the building gets turned over.


With this feature, the 21- cylinder is master keyed with 3 small ball bearings in one of the chambers. The plug is drilled in two places along both sides of the same

chamber containing the balls. This allows the construction master key to be used, while leaving these balls in the chamber above the plug when the key is rotated. When it is time to void the construction key, by simply using the change (day) key these balls will fall into the holes in the plug. The construction master key will now no longer operate the lock.

Field construction (21- lost ball) keying can also be easily accomplished with the # 439 LOST BALL REKEYING KIT. The kit includes a drilling block, knurled pin, 500 balls and drill with collar.


Orders with 21- will have all change keys shipped separately from hardware. New key systems provided with six construction master keys unless otherwise specified.

Additions to orders to existing systems are not provided with construction masters unless ordered separately.




Cutaway cylinder showing construction master key being used. Note the two empty holes on either side of the chamber.


To Void Construction Key




Change key inserted in cylinder



As change key rotates, construction balls fall into hole in the side of plug



Change key rotated to position for extraction



Construction key inserted after balls are trapped. Driver now extends into plug chamber. Construction key will not rotate

22- Prefix Split Key Construction Keying

The 22- prefix for split-key construction keying is available only for **existing systems**. When construction is completed, each cylinder must have the construction split key removed with extractor tool part number 14-0070 (one supplied per order). Orders with 22- prefix will have all change keys shipped separately from hardware. Not available with XC or Signature cylinders, non-SARGENT keyways or with cylinders used in other manufacturers' locks. Construction Master Keys part number 14-0069 must be ordered separately.


439 Construction Keying Kit (Lost Ball)

This kit is designed to allow field construction master keying of SARGENT conventional, Signature and XC cylinders.

Each kit includes:

1. Drilling block
2. Drill bit
3. Knurled pin
4. Hex key (not shown)
5. Collar & Set screw Assy.
6. 500 each balls, P/N 13-1103 (not shown)


Drill block shown with plug being prepared for field construction keying



Bitting Dimensions, Pins and Springs

Cylinders and Components

SARGENT®
ASSA ABLOY



6 PIN POSITIONS Shown, depth and spacing are the same for 5 & 7 pin

Depth tolerance
± .002", spacing
tolerance ± .001"

Cut#	1	2	3	4	5	6	7	8	9	10
X	.330	.310	.290	.270	.250	.230	.210	.190	.170	.150

Above bitting dimensions are for SARGENT cylinders in the following keyway families: A, B, C, G, H, K, L, M, N, R, V

Springs

13-0265 used in all cylinders except 3rd & 4th position of 6300 and 10-6300 cores for factory pinned cores prior to January 09

13-0487 used in 3rd & 4th position of 6300, 10-6300 cores for field rekeying for factory keyed cores prior to January 09

13-1769 spring used in all chambers and with standard master pins as drivers of master keyed 6300, 10-6300 & 11-6300 cylinders since January 2009

Brass Pins for SARGENT Keyways

Bottom Pins		Length	Master/Driver Pins		Length
SIZE #1	13-0064	.170	SIZE #2	13-0051	.040
SIZE #2	13-0065	.190	SIZE #3	13-0052	.060
SIZE #3	13-0066	.210	SIZE #4	13-0053	.080
SIZE #4	13-0067	.230	SIZE #5	13-0054	.100
SIZE #5	13-0068	.250	SIZE #6	13-0055	.120
SIZE #6	13-0069	.270	SIZE #7	13-0056	.140
SIZE #7	13-0070	.290	SIZE #8	13-0057	.160
SIZE #8	13-0071	.310	SIZE #9	13-0058	.180
SIZE #9	13-0072	.330	SIZE #10	13-0059	.200
SIZE #10	13-0073	.350	SIZE #11	13-0060	.220
			SIZE #12	13-0061	.240
			SIZE #13	13-0062	.260
			SIZE #14	13-0063	.280

All pins .115 diameter

10-34 & 10-40 Signature UL 437 Pins

Hardened stainless steel bottom pins used only in the 1st chamber of 10-UL 40 Series mortise cylinders & 10-UL 34 Series rim cylinders.

SIZE #1	13-1210	SIZE #6	13-1215
SIZE #2	13-1211	SIZE #7	13-1216
SIZE #3	13-1212	SIZE #8	13-1217
SIZE #4	13-1213	SIZE #9	13-1218
SIZE #5	13-1214		

Stainless spool driver 13-1223 used in all position 10-UL 40 Series and 10-UL 34 Series cylinders.

6300 & 10-6300 Large Format Interchangeable (Removable) Core Hollow Top Pins

Different top pins were used only in the 3rd and 4th positions of 6300, 10-6300 of factory keyed LFIC (Removable) Cores prior to Jan 2009. All other chambers use standard top pins.

SIZE #3	13-1229	SIZE #8	13-1238
SIZE #4	13-1234	SIZE #9	13-1239
SIZE #5	13-1235	SIZE #10	13-1240
SIZE #6	13-1236	SIZE #11	13-1761
SIZE #7	13-1237		

Pins Supplied with Keying Kits

437C/437S

Size #	Bottom Pins	Master/Driver Pins	Hollow Top Pins
1	13-0064		used in factory keyed cylinders prior to January 09
2	13-0065	13-0051	
3	13-0066	13-0052	13-1229
4	13-0067	13-0053	13-1234
5	13-0068	13-0054	13-1235
6	13-0069	13-0055	13-1236
7	13-0070	13-0056	13-1237
8	13-0071	13-0057	13-1238
9	13-0072	13-0058	13-1239
10	13-0073	13-0059	13-1240
11		13-0060	
12		13-0061	
13		13-0062	
14		13-0063	

437RC/UL

Conventional, Signature & LFIC (Removable) Core Keying Kits & Depth Key Sets

Cylinders and Components

SARGENT®
ASSA ABLOY

437C Conventional Keying Kit

Includes the brass pins, springs and tools needed to rekey SARGENT conventional, XC cylinders(Except SFIC) and interchangeable cores master keyed after January 2009. This heavy duty steel kit prevents pins from mixing. The kit includes 100 each of top springs 13-0265, 100 each 13-1769 springs used with standard drivers in the (10-) 6300 cores and 100 each of bottom and master/driver pins used in the following multi-family keyways: LA, RA, HA, CA, AA, BA, GA, KA, NA and VA.

NOTE: When re-pinning SARGENT 6300 Large Format Interchangeable (Removable) Core cylinders made before January 2009 they contained special hollow drivers, the 437RC/UL supplemental pinning kit is required.

Tools included with kit are:

- Tweezers, 13-0498
- Bitting Gauge #435
- Loading Thimble ("Plug Holder" LT2)
- Loading Rod for 6, 8, 10, 11, mortise & rim cylinders, 13-1034
- Loading Rod for 480, 470, 460 and 6300 Cores, 13-1035
- Loading Rod Blades 13-1138 and 13-1037
- See Table on Page 13 for pins included

When pins are sold separately, they are packaged in easy to see and use foil & plastic packages in quantities of 100 per size.

437S Signature Keying Kit

Used to service SARGENT Signature cylinders. Includes all of the same components as the 437C plus:

- 100 Blocking Bar Springs, 13-0986
- 10 each Blocking Bars, 13-1109
- 1 each Field Service Tool, 13-3916

NOTE: When repining 10-6300 Signature Large Format Interchangeable (Removable) Core cylinders made before January 2009 they contained special hollow drivers, the 437RC/UL supplemental pinning kit is required.

437 RC/UL Large Format Interchangeable (Removable) Core Keying Kit

Use with the 437C or 437S kit. Includes additional pins to repin SARGENT 6300 and 10-6300 Large Format Interchangeable (Removable) Core cylinders that have been pinned using the hollow drivers.

The kit includes special hollow top pins and springs which were used in the 3rd and 4th chambers of master keyed cores prior to January 2009.

These pins are in the same increments as standard pins.

Each kit includes:

- 100 each hollow top pin springs, 13-0487
- 50 each cylinder retainers, 01-0660
- 50 each (hollow top pins). See Table on Page 13

10-34 and 10-40 Series Signature UL437 Pins

The 437 RC/UL kit has extra room for optional hardened stainless steel bottom pins used when repinning SARGENT Signature UL437 Listed cylinders. These are ordered separately in quantities of 25. See Table on Page 13.

437BR Bump Resistant Re-Pinning Kit

The 437BR Kit to convert existing cylinders to bump resistant cylinders. Order as a 437BR Kit (See page 10 for additional information)

Depth Key Sets

Used for manual code key cutting. Each set includes 10 each SARGENT unwarded 6 pin keys. Each different key is cut with all the same bittings from 0 through 9. Order as "Depthkeys".

Cylinder Spray Lubricant

3.0 oz aerosol pin number 18-0070

Cylinder Spray Cleaner/Deicer 3.0 OZ aerosol pin number 18-0435



437C shown



Key Blanks/Key Sections, Bitting Lists

Cylinders and Components


5 Pin		6 Pin		7 Pin	
Key Blank	Key Section	Key Blank	Key Section	Key Blank	Key Section
265	U R	6265	U R S		LD LH LM LDH LDM LHM LN RD RH RM RDH RDM RHM RN
270	LD LH LM LDH LDM LHM LN RD RH RM RDH RDM RHM RN	6270	HD HH HM HDH HDM LHM LN RD RH RM RDH RDM RHM RN	7270	
				7273	CD CH CM CDH CHM CN
273	CD CH CM CDH CHM CN	6273	CD CH CM CDH CHM CN		LA LB LC LE LF LG LJ LK LL RA RB RC RE RF RG RJ RK RL
275	S		HA HB HC HE HF HG HJ HK HL	7275	
275	LA LB LC LE LF LG LJ LK LL RA RB RC RE RF RG RJ RK RL	6275	RA RB RC RE RF RG RJ RK RL	7278	CA CB CC CE CF CG CJ CK CL CR
278	CA CB CC CE CF CG CJ CK CL CR	6278	CA CB CC CE CF CG CJ CK CL CR		

BITTING LISTS

Paper bitting lists provided at no charge for factory corresponding keyed orders when requested at time of hardware order. An owners letter of authorization must be attached to all purchase orders Existing key system bittings lists also available contact key records for more information.


ASSA ABLOY, the global leader in door opening solutions

For Multiplex Masterkey Systems (L keyway family shown, others similar)



Multi Keyway Systems

- L – System Stock Keyways
- C – System Hotel Keyway (Furnished in Large Bow only)
- H – System Contract Master Key Systems
- R – System Contract MasterKey Systems



Standard 6 pin

Large Bow approximately 15% larger than standard bow. Provided for SARGENT "C" family as standard.

Single Keyway Sections

- R Section
- S Section
- U Section
- CR Section

Restricted Keyways: Restricted keyways are SARGENT (factory) controlled geographically to limit sales and prevent unauthorized key duplication.

For availability of restricted keyways and key sections, contact SARGENT Key Records Department.

Orders for restricted keyway systems, key blanks and cylinders, require a letter of authorization from the system owner.

Visual Key Control and Tamper Proof Packaging

Cylinders and Components

SARGENT®
ASSA ABLOY

Visual Key Control (Stamping)

To allow for easier key and cylinder identification, SARGENT offers the option for permanent stamping of keys and/or cylinder with industry standard alpha-numeric keyset symbols.

Non-visual key control stamped change (day) keys include bitting numbers as standard, (Item A) unless specified in keying order lead sheet submitted with order requesting to be omitted and key set substituted.


SFIC and Signature change keys are stamped with key set symbols as standard.

Master level keys do not include bitting numbers. Master level keys include system register numbers stamped on the first line, and the standard visual key control designations on the second line (Item B).

Up to 7 characters available for permanent stamping for Visual Key Control

- Key and cylinder identified by industry standard alpha-numeric keyset symbols
- Easy visual identification on the face of the plug (Item C or Item G or H) not available with XC or Signature cylinders
- Concealed stamping on mortise and rim cylinders and bored lock cylinders available on the slide only (Item D or I)
- Cylinder-slide stamping available on 5100 and 6300 SARGENT Large Format Interchangeable (Removable) Coress, bored lock, mortise/rim cylinders (Item D, E & I)
- Core side engraving available for 7300B Series up to 7 characters (Item F)
- Special key stampings available, such as "DO NOT DUPLICATE" or "CITY OF PHOENIX"
- XC and Signature cylinders not available with visual plug stamping
- XC and Signature cylinders available with only concealed slide stamping (Item D, E and I) only
- Signature Large Format Interchangeable (Removable) Cores 10-6300 available with cylinder slide stamping (Item E, I D)

NOTE: SARGENT will stamp alternate identity codes on cylinders and/or keys whenever requested. This alternate stamping can not be different if both are to be stamped. Master Level Keys can also be stamped with a single alternate code.



Tamper Proof Packaging

For the highest level of security for the end user, Tamper Proof Packaging is used on all Master Keys, Signature key blanks and all restricted key blanks. This heat sealed shrink wrap identified with "SARGENT Sealed For Your Security" provides assurance of the integrity of the factory generated key system.

Master Keying and Cylinder Terms

Cylinders and Components

SARGENT requires all orders containing Master Keying details to be submitted using the industry standard D.H.I. ANSI/BHMA format. Key Symbols used on a master keyed order require combinations of letters and/or letters and numbers.

For complete details on proper structuring format of key symbols refer to:

D.H.I. Handbook Section 8 Finish Hardware KEYING SYSTEMS AND NOMENCLATURE or,
ANSI/BHMA Standard A156.28, AMERICAN NATIONAL STANDARDS FOR KEYING SYSTEMS.

Or contact SARGENT for assistance.

Basic Keying Terms

Keys and terms	Abbreviation	Definition
Change key	CK	Individual lock key
Masterkey	MK	Operates any given quantity of cylinders with different key changes
Grand Masterkey	GMK	Operates all individual locks already operated by masterkey(s)
Great Grand Masterkey	GGMK	Operates all locks under the various masterkey(s) and grand master key(s) already established
Emergency Key	EMK	Operates hotel locks having shut out feature which blocks entry by all other keys
Construction key	CMK	Operates all cylinders designated for a temporary period during construction
Control Key	CTL	Key to install or remove interchangeable or removable cores
Keyway	KWY	Broaching in a cylinder plug
Key section	KWY	Sidewarding on key to match broaching in plug
Single keyed	SKD	Cylinders operated by their change key only; not operated by any master key


Cylinder Terms

ALOA* adopted terms	Alternate terms
Shell	Cylinder body, Cylinder shell
Plug	Barrel, Cylinder barrel
Tail Piece	Connecting bar
Bottom Pins	Key pin, Ball end pins
Master Pins	Splits, Chips
Top Pins	Drivers
Change Key	Day key
Key Cut	Bit


* Associated Locksmiths of America

Examples of Master Key System Levels and Symbol Structure**


Level 2



Level 3



Level 4



** Master key system levels greater than Level 4 are not recommended. Contact SARGENT Key Records for additional information.

SARGENT Manufacturing Company
100 Sargent Drive, New Haven, CT 06511 USA
800-727-5477 • www.sargentlock.com

Founded in the early 1800s, SARGENT® is a market leader in locksets, cylinders, door closers, exit devices, electro-mechanical products and access control systems for new construction, renovation, and replacement applications. The company's customer base includes commercial construction, institutional, and industrial markets.

Copyright © 2006, 2008-2012, Sargent Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Sargent Manufacturing Company is prohibited.

ASSA ABLOY is the global leader in door opening solutions, dedicated to satisfying end-user needs for security, safety and convenience.